

M1205-T80L-1, -2

Acousto-Optic Modulator



0426


APPLICATIONS

- Intensity Modulator
- Low resolution Deflector
- Frequency Shifter

RF Drive Electronics

Digital modulation	522F-1 / -2, RG3-080
Analog modulation	532F-1 / -2, RG3-080
Dual modulation	552F-1 / -2 RG5-080
Tuneable with modulation	RF5-80T-2, iCSA-100-1-1

OUTLINE DRAWING




M3 metric fixing threads available. Please include the option suffix (M)

Note: Mount device to heat conducting surface

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
ISOMET CORP, 10342 Battlevue Parkway, Manassas, VA 20109, USA.
Tel: (703) 321 8301 Fax: (703) 321 8546
E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.
In-house: Crystal Growth,
Optical Polishing,
A/R coating, Vacuum Bonding



M1205-T80L-1, -2

Acousto-Optic Modulator



0426


SPECIFICATIONS

A/R Operating Wavelengths:	500-640nm
Interaction Medium:	Tellurium Dioxide (TeO ₂)
Acoustic Velocity:	4.2mm/μs
Active Aperture Height (H):	-1: 1.0mm
	or -2: 2.0mm
Polarization:	Any, vertical preferred.
Centre Frequency (CF):	80MHz
RF Bandwidth (minimum):	30MHz (+/- 15MHz)
Input Impedance:	50Ω Nominal
VSWR:	<1.5:1 @ 80MHz
DC Contrast Ratio:	>1000:1 min (>2000:1 typical)

PERFORMANCE vs. WAVELENGTH

Wavelength:		515nm	589nm	640nm
RF Drive Power, typ':	(-1)	0.35W	0.53W	0.63W
	(-2)	0.7W	1.1W	1.3W
Bragg angle:		5.1 mrad	5.6 mrad	6.1 mrad
Beam Separation:		10.1 mrad	11.2 mrad	12.2 mrad
Static Insertion Loss:		< 3%	< 3%	< 3%

PERFORMANCE vs. BEAM DIAMETER at 532nm



ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
 ISOMET CORP, 10342 Battleview Parkway, Manassas, VA 20109, USA.
 Tel: (703) 321 8301 Fax: (703) 321 8546
 E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.
 In-house: Crystal Growth,
 Optical Polishing,
 A/R coating, Vacuum Bonding